

Housing	PC, PMMA Diffusor
Colour	Black, White, Grey
Fixture type	3-phase track light
Module	Samsung
Driver	Triac Dimmable, TUV, ENEC
Lumen output	3500lm
CCT	2700K, 3000K, 3500K, 4000K
CRI	>93Ra
Beam angles	120°
Adapter	3-phase adapter included
Rotatable	350°
Tiltable	80°
Expected Lifetime	50.000h L80/B10
Photobiological safety	RG1 unlimited
Power factor	> 0.95
UGR	< 19
Colour consistency	3 SDCM
Warranty	5 years warranty on LED module and driver



LED MODULES

Standard



OPTIONS

Dimmable

Casambi



DIMENSIONS

DIAM. 330mm - L. 180mm

LED MODULE OPTIONS

[illegible]

LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 3500K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

¹⁾ Lumen output of LED module (COB)

²⁾ Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

³⁾ Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.